

SB-5642LCM

4x2 HDMI Matrix Switcher



Input : 4x HDMI
Output : 2x HDMI

PRO MATRIX SWITCHER




03

INTRODUCTION

The SB-5642LCM is high-performance 4x2 matrix routing switcher for HDMI™ signals. This switcher supports data rates up to 2.25 Gbps, enabling 1080p HDMI™ formats and UXGA / WUXGA / DVI resolution to any HD displays. High Definition Digital signals can be selected and distributed to any outputs simultaneously. The Switcher is certified and fully HDMI™ and HDCP compliant, with CE,FCC certification. Support high resolution HDMI™ sources routed to HDMI™ displays, monitors, projector or audio receivers. The EDID can be selected between seven (7) different modes and learning mode. Control is provided via front panel push buttons, IR remote or via RS-232. A RS-232 Windows GUI interface is provided for matrix routing.

DIAGRAM TYPICAL



FEATURES

- Support (4)x HDMI digital source devices Matrix switched to (2)x HDMI destinations
- HDMI Digital video/multi-channel audio format, DVI 1.0 format and HDCP 1.3 compliant
- Support HDMI/DVI high definition resolutions 408p, 720p, 1080i/1080p up to 36 bit, 3D formats
- Support link speeds of up to 2.25 Gbps (link clock rate of 250 MHZ)
- Wide range of HD resolutions from PC XGA to WUXGA 1920x1200 and HDTV/DTV HDMI resolutions 480i/480p, 576i/576p, 720p, 1080i/p
- Audio Supports Dolby TrueHD, Dolby Digital, Dolby Digital Plug/ex, DTS, DTS-HD, DTS-HD Master, DTS-EX, PCM, PCM2, LPCM2.
- Support IR Remote and IR Extender with distance 300M Maximum
- Various User Interface controls :
 - Windows based GUI control via RS-232 port
 - Front Panel push buttons
 - IR wireless remote controller
 - IR External port (Switch Control)
 - Third party RS-232 controller (via simple ASCII)
- Compatible with full HD high resolution Video player device and LCD / Plasma monitor displays or Projector
- Direct selection and confirm via Front push buttons with LED readout
- Infrared : IR remote control (38KHz)
- Support world wide eight (8) select embedded EDID modes
- Support seven (7) control function key :
 - ALL / OFF / RECALL / ENTER / MEMORY / LOCK / EDID
- Support RS-232 interface control AP driver for PC 95/98/2000/XP/7/8 A Windows-based control software Driver packaged
- Support desktop with Ear mount and 19 inch 1U Rack mountable type panel
- Support Lower power consumed full load under 1800 mA
- Power supply DC12V, Universal Type Switch 100~240VAC, 50/60Hz

SPECIFICATIONS

| | |
|----------------------------|--|
| Type of HDMI Switcher | (4)x inputs To (2)x Outputs HDMI Matrix Switcher |
| HDMI Support | HDMI Video 0.5~1Vpp, DDC5Vpp, HDMI V1.4a, 3D formats |
| HDCP / CEC Support | HDCP 1.3 Compliant, CEC Compliant |
| Video Bandwidth | Double Data Rates: 250Mhz, Total 2.25Gbps bandwidth |
| Digital Video Support | HD:480i/480p/720p/1080i/p up to 36bit deep color |
| Input | (4)x HDMI (HDMI or DVI digital source) |
| Output | (2)x HDMI (To 2x Destinations) |
| Switch Controls | 1x Select & Function buttons on front panel (Data status via LED panel readout) 1x IR Remote Controller (switch control) 1x IR External port (switch control via 3.5mm OD Jack) 1x RS 232 series interface (switch control) |
| Source Status | Input status LEDs indicates presence of a live signal |
| (13) Function Control Keys | 1.ALL, 2.OFF, 3.RECALL, 4.ENTER, 5.MEMORY, 6.LOCK, 7.EDID, 8.Destination button (1) thru (2), 9.Source button (1) thru (4) |
| Infrared Frequency | 38 Khz |
| IR External Distance | ~984 feet / 300 meters maximum |
| HDMI I/O Connector | HDMI Type A - SMD 19pin Female Type |
| Temperature | Operating Temperature 32°F - 100°F (0°C - 32°C) |
| Safety Approvals | CE, FCC, REACH |
| Rack Mount Bracket | 19 inch 1U High Rack Mount Bracket (1U-440L) |
| Dimension (WxDxH) | 17.4" x 9.96" x 1.73" (442mm x 253mm x 44mm) |
| Weight | 2.5 kg / 5.51 lb |
| Power Supply | DC 12V, @5A (World Wide Universal AC 100~240V 50/60Hz) |